

Package: mapdeck (via r-universe)

October 14, 2024

Type Package

Title Interactive Maps Using 'Mapbox GL JS' and 'Deck.gl'

Version 0.3.6

Date 2024-07-02

Description Provides a mechanism to plot an interactive map using 'Mapbox GL' (<<https://docs.mapbox.com/mapbox-gl-js/api/>>), a javascript library for interactive maps, and 'Deck.gl' (<<https://deck.gl/>>), a javascript library which uses 'WebGL' for visualising large data sets.

License GPL-3

URL <https://symbolixau.github.io/mapdeck/articles/mapdeck.html>

BugReports <https://github.com/SymbolixAU/mapdeck/issues>

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0)

SystemRequirements C++14

Imports colourvalues (>= 0.3.9), googlePolylines (>= 0.7.2), geojsonsf (>= 2.0.3), htmlwidgets, jsonify (>= 1.2.2), magrittr, Rcpp (>= 1.0.10), shiny, sfheaders (>= 0.4.4)

RoxygenNote 7.2.3

LinkingTo BH, colourvalues (>= 0.3.9), geojsonsf (>= 2.0.3), geometries (>= 0.2.4), interleave (>= 0.1.2), jsonify (>= 1.2.2), rapidjsonr, Rcpp (>= 1.0.10), sfheaders (>= 0.4.4), spatialwidget (>= 0.2.5)

Suggests covr, googleway, jsonlite, knitr, rmarkdown, spatialwidget, testthat

VignetteBuilder knitr

Repository <https://symbolixau.r-universe.dev>

RemoteUrl <https://github.com/symbolixau/mapdeck>

RemoteRef HEAD

RemoteSha 3d2d5abff0450a25cd926ac9ad31b95f303343d3

Contents

add_animated_arc	3
add_animated_line	7
add_arc	10
add_bitmap	15
add_cesium	16
add_column	17
add_dependencies	21
add_geojson	22
add_greatcircle	27
add_grid	31
add_h3	35
add_heatmap	38
add_hexagon	40
add_i3s	44
add_line	45
add_mesh	48
add_path	51
add_pointcloud	56
add_polygon	59
add_scatterplot	63
add_screengrid	67
add_sf	70
add_terrain	70
add_text	72
add_title	75
add_trips	76
capitals	80
city_trail	81
clear_animated_arc	81
clear_legend	82
clear_tokens	83
geojson	83
legend_element	84
light_settings	85
mapdeck	85
mapdeck-shiny	87
mapdeck_dependencies	87
mapdeck_dispatch	88
mapdeck_legend	88
mapdeck_style	89
mapdeck_tokens	90
mapdeck_update	90
mapdeck_view	91
melbourne	91
melbourne_mesh	92
roads	92

`add_animated_arc` 3

<code>road_safety</code>	93
<code>set_token</code>	93
<code>update_style</code>	94
<code>%>%</code>	94

Index 95

`add_animated_arc` *Add animated arc*

Description

The Arc Layer renders raised arcs joining pairs of source and target coordinates

Usage

```
add_animated_arc(  
  map,  
  data = get_map_data(map),  
  layer_id = NULL,  
  origin,  
  destination,  
  id = NULL,  
  stroke_from = NULL,  
  stroke_from_opacity = NULL,  
  stroke_to = NULL,  
  stroke_to_opacity = NULL,  
  stroke_width = NULL,  
  frequency = 1,  
  animation_speed = 3,  
  trail_length = 5,  
  tilt = NULL,  
  height = NULL,  
  tooltip = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  legend = F,  
  legend_options = NULL,  
  legend_format = NULL,  
  palette = "viridis",  
  na_colour = "#808080FF",  
  update_view = TRUE,  
  focus_layer = FALSE,  
  transitions = NULL,  
  digits = 6,  
  brush_radius = NULL  
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
origin	vector of longitude and latitude columns, and optionally an elevation column, or an sfc column
destination	vector of longitude and latitude columns, and optionally an elevatino column, or an sfc column
id	an id value in data to identify layers when interacting in Shiny apps.
stroke_from	column of data or hex colour to use as the staring stroke colour. IIf using a hex colour, use either a single value, or a column of hex colours on data
stroke_from_opacity	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_to	column of data or hex colour to use as the ending stroke colour. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_to_opacity	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_width	width of the stroke in pixels
frequency	column of data, or a single value indicating the number of arcs generated in each animation
animation_speed	the speed of animation
trail_length	the length of trail of each arc
tilt	value to tilt the arcs to the side, in degrees [-90, 90]
height	value to multiply the height.
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend

palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
transitions	list specifying the duration of transitions.
digits	number of digits for rounding coordinates
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed

Details

add_arc supports POINT sf objects

MULTIPOINT objects will be treated as single points. That is, if an sf object has one row with a MULTIPOINT object consisting of two points, this will be expanded to two rows of single POINTs. Therefore, if the origin is a MULTIPOINT of two points, and the destination is a single POINT, the code will error as there will be an uneven number of rows

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- `css` - a string of valid css for controlling the appearance of the legend
- `title` - a string to use for the title of the legend
- `digits` - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- `fill_colour`
- `stroke_colour`

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The `id` is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where `'map'` is the `map_id` supplied to `mapdeckOutput()`, and `'arc'` is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

url <- 'https://raw.githubusercontent.com/plotly/datasets/master/2011_february_aa_flight_paths.csv'
flights <- read.csv(url)
flights$id <- seq_len(nrow(flights))
flights$stroke <- sample(1:3, size = nrow(flights), replace = TRUE)
flights$info <- paste0("<b>", flights$airport1, " - ", flights$airport2, "</b>")

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
  add_animated_arc(
    data = flights
    , layer_id = "arc_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
    , trail_length = 10
    , tooltip = "info"
    , auto_highlight = TRUE
    , legend = TRUE
    , legend_options = list(
      stroke_from = list( title = "Origin airport" ),
      css = "max-height: 100px;" )
  )

## faster animation_speed
mapdeck( style = mapdeck_style("dark")) %>%
  add_animated_arc(
    data = flights
    , layer_id = "arc_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
    , trail_length = 10
    , animation_speed = 15
  )
```

add_animated_line	<i>Add Animated line</i>
-------------------	--------------------------

Description

The Line Layer renders raised lines joining pairs of source and target coordinates

Usage

```
add_animated_line(  
  map,  
  data = get_map_data(map),  
  layer_id = NULL,  
  origin,  
  destination,  
  id = NULL,  
  stroke_colour = NULL,  
  stroke_width = NULL,  
  stroke_opacity = NULL,  
  frequency = 1,  
  animation_speed = 3,  
  trail_length = 5,  
  tooltip = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  palette = "viridis",  
  na_colour = "#808080FF",  
  legend = FALSE,  
  legend_options = NULL,  
  legend_format = NULL,  
  update_view = TRUE,  
  focus_layer = FALSE,  
  digits = 6,  
  transitions = NULL,  
  brush_radius = NULL  
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system

<code>layer_id</code>	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
<code>origin</code>	vector of longitude and latitude columns, and optionally an elevation column, or an <code>sfc</code> column
<code>destination</code>	vector of longitude and latitude columns, and optionally an elevation column, or an <code>sfc</code> column
<code>id</code>	an id value in data to identify layers when interacting in Shiny apps.
<code>stroke_colour</code>	variable or hex colour to use as the ending stroke colour.
<code>stroke_width</code>	width of the line in metres
<code>stroke_opacity</code>	Either a string specifying the column of data containing the opacity of each shape, or a single value in $[0, 255]$, or $[0, 1)$, to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
<code>frequency</code>	column of data, or a single value indicating the number of arcs generated in each animation
<code>animation_speed</code>	the speed of animation
<code>trail_length</code>	the length of trail of each arc
<code>tooltip</code>	variable of data containing text or HTML to render as a tooltip
<code>auto_highlight</code>	logical indicating if the shape under the mouse should auto-highlight
<code>highlight_colour</code>	hex string colour to use for highlighting. Must contain the alpha component.
<code>palette</code>	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between $[0, 255]$, where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
<code>na_colour</code>	hex string colour to use for NA values
<code>legend</code>	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
<code>legend_options</code>	A list of options for controlling the legend.
<code>legend_format</code>	A list containing functions to apply to legend values. See section <code>legend</code>
<code>update_view</code>	logical indicating if the map should update the bounds to include this layer
<code>focus_layer</code>	logical indicating if the map should update the bounds to only include this layer
<code>digits</code>	number of digits for rounding coordinates
<code>transitions</code>	list specifying the duration of transitions.
<code>brush_radius</code>	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed

Details

add_line supports POINT sf objects

MULTIPOINT objects will be treated as single points. That is, if an sf object has one row with a MULTIPOINT object consisting of two points, this will be expanded to two rows of single POINTs. Therefore, if the origin is a MULTIPOINT of two points, and the destination is a single POINT, the code will error as there will be an uneven number of rows

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

url <- 'https://raw.githubusercontent.com/plotly/datasets/master/2011_february_aa_flight_paths.csv'
flights <- read.csv(url)
flights$id <- seq_len(nrow(flights))
flights$stroke <- sample(1:3, size = nrow(flights), replace = TRUE)

mapdeck(style = mapdeck_style("dark"), pitch = 45 ) %>%
  add_animated_line(
    data = flights
    , layer_id = "line_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_colour = "airport1"
    , stroke_width = "stroke"
    , auto_highlight = TRUE
    , trail_length = 1
    , animation_speed = 1
  )

## Using a 2-sfc-column sf object
library(sfheaders)

sf_flights <- sfheaders::sf_point( flights, x = "start_lon", y = "start_lat", keep = TRUE )
destination <- sfheaders::sfc_point( flights, x = "end_lon", y = "end_lat" )

sf_flights$destination <- destination

mapdeck() %>%
  add_animated_line(
    data = sf_flights
    , origin = 'geometry'
    , destination = 'destination'
    , layer_id = 'arcs'
    , stroke_colour = "airport1"
    , trail_length = 1
    , animation_speed = 2
  )
```

`add_arc`*Add arc*

Description

The Arc Layer renders raised arcs joining pairs of source and target coordinates

Usage

```
add_arc(  
  map,  
  data = get_map_data(map),  
  layer_id = NULL,  
  origin,  
  destination,  
  id = NULL,  
  stroke_from = NULL,  
  stroke_from_opacity = NULL,  
  stroke_to = NULL,  
  stroke_to_opacity = NULL,  
  stroke_width = NULL,  
  tilt = NULL,  
  height = NULL,  
  tooltip = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  legend = F,  
  legend_options = NULL,  
  legend_format = NULL,  
  palette = "viridis",  
  na_colour = "#808080FF",  
  update_view = TRUE,  
  focus_layer = FALSE,  
  transitions = NULL,  
  digits = 6,  
  brush_radius = NULL,  
  ...  
)
```

Arguments

<code>map</code>	a mapdeck map object
<code>data</code>	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system

layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
origin	vector of longitude and latitude columns, and optionally an elevation column, or an sfc column
destination	vector of longitude and latitude columns, and optionally an elevatino column, or an sfc column
id	an id value in data to identify layers when interacting in Shiny apps.
stroke_from	column of data or hex colour to use as the staring stroke colour. IIf using a hex colour, use either a single value, or a column of hex colours on data
stroke_from_opacity	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_to	column of data or hex colour to use as the ending stroke colour. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_to_opacity	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_width	width of the stroke in pixels
tilt	value to tilt the arcs to the side, in degrees [-90, 90]
height	value to multiply the height.
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
legend	either a logical indiciating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
palette	string or matrix. String will be one of colourvalues::colour_palettes(). A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. list(fill_colour = "viridis", stroke_colour = "inferno")
na_colour	hex string colour to use for NA values
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
transitions	list specifying the duration of transitions.

digits	number of digits for rounding coordinates
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_arc supports POINT sf objects

MULTIPOINT objects will be treated as single points. That is, if an sf object has one row with a MULTIPOINT object consisting of two points, this will be expanded to two rows of single POINTs. Therefore, if the origin is a MULTIPOINT of two points, and the destination is a single POINT, the code will error as there will be an uneven number of rows

data

If data is a simple feature object, you need to supply the origin and destination columns, they aren't automatically detected.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for arc

```
list( origin = 0, destination = 0, stroke_from = 0, stroke_to = 0, stroke_width = 0 )
```

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

url <- 'https://raw.githubusercontent.com/plotly/datasets/master/2011_february_aa_flight_paths.csv'
flights <- read.csv(url)
flights$id <- seq_len(nrow(flights))
flights$stroke <- sample(1:3, size = nrow(flights), replace = TRUE)
flights$info <- paste0("<b>", flights$airport1, " - ", flights$airport2, "</b>")

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
  add_arc(
    data = flights
    , layer_id = "arc_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
    , tooltip = "info"
    , auto_highlight = TRUE
    , legend = TRUE
    , legend_options = list(
      stroke_from = list( title = "Origin airport" ),
      css = "max-height: 100px;" )
  )

mapdeck( style = mapdeck_style("dark")) %>%
  add_arc(
    data = flights
    , layer_id = "arc_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
  )

## Arcs can have an elevated start & destination
flights$start_elev <- sample(100000:1000000, size = nrow(flights), replace = TRUE )
```

```
mapdeck( style = mapdeck_style("dark")) %>%
  add_arc(
    data = flights
    , layer_id = "arc_layer"
    , origin = c("start_lon", "start_lat", "start_elev")
    , destination = c("end_lon", "end_lat", "start_elev")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
  )
```

```
## Using a 2-sfc-column sf object
library(sfheaders)
```

```
sf_flights <- sfheaders::sf_point(
  flights
  , x = "start_lon"
  , y = "start_lat"
  , z = "start_elev"
  , keep = TRUE
)
destination <- sfheaders::sfc_point(
  flights
  , x = "end_lon"
  , y = "end_lat"
  , z = "start_elev"
)
```

```
sf_flights$destination <- destination
```

```
mapdeck(
) %>%
  add_arc(
    data = sf_flights
    , origin = 'geometry'
    , destination = 'destination'
    , layer_id = 'arcs'
    , stroke_from = "airport1"
    , stroke_to = "airport2"
  )
```

```
## using a brush
```

```
mapdeck(
  , style = mapdeck_style("light")
) %>%
  add_arc(
    data = sf_flights
    , origin = 'geometry'
    , destination = 'destination'
    , layer_id = 'arcs'
    , stroke_from = "airport1"
```

```

    , stroke_to = "airport2"
    , stroke_width = 4
    , brush_radius = 500000
)

```

add_bitmap

Add bitmap

Description

Adds an image to a map

Usage

```

add_bitmap(
  map,
  image,
  bounds,
  desaturate = 0,
  transparent_colour = "#000000",
  tint_colour = "#FFFFFF",
  layer_id = NULL,
  update_view = TRUE,
  focus_layer = FALSE
)

```

Arguments

map	a mapdeck map object
image	url to an image to use on the map
bounds	coordinates of the bounding box of the image [left, bottom, right, top]
desaturate	the desatruation of the bitmap, in range [0,1], 0 being the original colour and 1 being greyscale
transparent_colour	the colour to use for transparent pixels as a hex string
tint_colour	the colour to tint the bipmap by, as a hex string
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer

Examples

```

set_token( "MAPBOX_TOKEN" )

mapdeck(location = c(-122.3, 37.8), zoom = 10) %>%
  add_bitmap(
    image = paste0(
      'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/',
      'website/sf-districts.png')
    , bounds = c(-122.519, 37.7045, -122.355, 37.829)
  )

mapdeck(location = c(-75.9, 40.9), zoom = 4) %>%
  add_bitmap(
    image = 'https://docs.mapbox.com/mapbox-gl-js/assets/radar.gif'
    , bounds = c(-80.425, 37.936, -71.516, 46.437)
  )

mapdeck(location = c(-75.9, 40.9), zoom = 4) %>%
  add_bitmap(
    image = 'https://docs.mapbox.com/mapbox-gl-js/assets/radar.gif'
    , bounds = c(-80.425, 37.936, -71.516, 46.437)
    , tint_colour = "#FF0000"
  )

mapdeck(location = c(-75.9, 40.9), zoom = 4) %>%
  add_bitmap(
    image = 'https://docs.mapbox.com/mapbox-gl-js/assets/radar.gif'
    , bounds = c(-80.425, 37.936, -71.516, 46.437)
    , desaturate = 1
  )

```

add_cesium

Add Cesium

Description

Renders 3D tiles data from Cesium ION assets. To use this layer you need a Cesium ION account <https://cesium.com/learn/cesiumjs-learn/cesiumjs-quickstart/#your-first-app>. This layer is experimental

Usage

```
add_cesium(map, data, point_size = 2, layer_id = NULL, ion_token = NULL)
```


Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
point_size	size of point in pixels
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
ion_token	ion asset token

Examples

```
## Melbourne point cloud
ion_asset <- 43978
ion_token <- "ION_TOKEN"
tile_data <- paste0("https://assets.ion.cesium.com/", ion_asset, "/tileset.json")

mapdeck(
  location = c(144.95, -37.82)
  , zoom = 14
  , pitch = 60
) %>%
  add_cesium(
    data = tile_data
    , ion_token = ion_token
  )
```

add_column

Add column

Description

The ColumnLayer can be used to render a heatmap of vertical cylinders. It renders a tessellated regular polygon centered at each given position (a "disk"), and extrude it in 3d.

Usage

```
add_column(
  map,
  data = get_map_data(map),
  polyline = NULL,
  lon = NULL,
  lat = NULL,
```

```

fill_colour = NULL,
fill_opacity = NULL,
stroke_colour = NULL,
stroke_opacity = NULL,
stroke_width = NULL,
radius = 1000,
elevation = NULL,
elevation_scale = 1,
coverage = 1,
angle = 0,
disk_resolution = 20,
tooltip = NULL,
auto_highlight = FALSE,
highlight_colour = "#AAFFFFFF",
layer_id = NULL,
id = NULL,
palette = "viridis",
na_colour = "#808080FF",
legend = FALSE,
legend_options = NULL,
legend_format = NULL,
update_view = TRUE,
focus_layer = FALSE,
digits = 6,
transitions = NULL,
brush_radius = NULL,
...
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
polyline	column of data containing the polylines
lon	column containing longitude values
lat	column containing latitude values
fill_colour	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_colour	variable of data or hex colour for the stroke. If used, elevation is ignored. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes.

	Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_width	width of the stroke in meters. If used, elevation is ignored. Default 1.
radius	in metres. Default 1000
elevation	the height the polygon extrudes from the map. Only available if neither stroke_colour or stroke_width are supplied. Default 0
elevation_scale	value to scale the elevations of the columns Default 1
coverage	radius multiplier, in range [0,1]. The radius of the disk is calculated by coverage * radius
angle	disk rotation, counter-clockwise, in degrees
disk_resolution	The number of sides to render the disk as. The disk is a regular polygon that fits inside the given radius. A higher resolution will yield a smoother look close-up, but also requires more resources to render.
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of colourvalues::colour_palettes(). A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. list(fill_colour = "viridis", stroke_colour = "inferno")
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_column supports POINT and MULTIPOINT sf objects

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where 'map' is the map_id supplied to `mapdeckOutput()`, and 'arc' is the layer you are clicking on

Examples

```
## Not run:

## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

df <- capitals
df$elev <- sample(50000:500000, size = nrow(df), replace = TRUE)
```

```
mapdeck(style = mapdeck_style("dark"), pitch = 45) %>%
add_column(
  data = df
  , lat = "lat"
  , lon = "lon"
  , elevation = "elev"
  , fill_colour = "lon"
  , disk_resolution = 20
  , radius = 100000
  , tooltip = "capital"
)

library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lon", y = "lat" )

sf$elev <- df$elev

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_column(
  data = sf
  , layer_id = "col_layer"
  , elevation = "elev"
  , radius = 100000
  , fill_colour = "country"
)

## End(Not run)
```

add_dependencies	<i>Add Dependencies</i>
------------------	-------------------------

Description

Adds the required mapdeck javascript dependencies to a map when not using a mapdeck map.

Usage

```
add_dependencies(map)
```

Arguments

map the map object to which dependencies will be added

Examples

```
## use with a google map from googleway
library(googleway)

set_key("GOOGLE_MAP_KEY")

google_map() %>%
  add_dependencies() %>%
  add_scatterplot(
    data = capitals
    , lon = "lon"
    , lat = "lat"
    , fill_colour = "country"
    , radius = 10000
  )
```

add_geojson

Add Geojson

Description

The GeoJson Layer takes in GeoJson formatted data and renders it as interactive polygons, lines and points

Usage

```
add_geojson(
  map,
  data = get_map_data(map),
  layer_id = NULL,
  stroke_colour = NULL,
  stroke_opacity = NULL,
  stroke_width = NULL,
  dash_size = NULL,
  dash_gap = NULL,
  fill_colour = NULL,
  fill_opacity = NULL,
  radius = NULL,
  elevation = NULL,
  extruded = FALSE,
  light_settings = list(),
  legend = F,
```

```

    legend_options = NULL,
    legend_format = NULL,
    auto_highlight = FALSE,
    tooltip = NULL,
    highlight_colour = "#AAFFFFFF",
    palette = "viridis",
    na_colour = "#808080FF",
    line_width_units = c("meters", "pixels"),
    line_width_scale = 1,
    line_width_min_pixels = 0,
    elevation_scale = 1,
    point_radius_scale = 1,
    point_radius_min_pixels = 1,
    update_view = TRUE,
    focus_layer = FALSE,
    digits = 6,
    transitions = NULL,
    ...
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. Can be a url to GeoJSON
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
stroke_colour	column of an sf object, or field inside a GeoJSON property to use for colour
stroke_opacity	column of an sf object, or field inside a GeoJSON property to use for opacity
stroke_width	column of an sf object, or field inside a GeoJSON property to use for width (in meters)
dash_size	size of each dash, relative to the width of the stroke
dash_gap	size of the gap between dashes, relative to the width of the stroke
fill_colour	column of an sf object, or field inside a GeoJSON property to use for colour
fill_opacity	column of an sf object, or field inside a GeoJSON property to use for opacity
radius	radius of points in meters. Default 1. See details
elevation	elevation of polygons. Default 0. See details
extruded	logical indicating if polygons should extrude from the map. If TRUE, stroke_colour for polygons is ignored
light_settings	list of light setting parameters. See light_settings
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend. A legend is only shown if you supply one of the colour arguments (fill or stroke)
legend_options	A list of options for controlling the legend.

legend_format	A list containing functions to apply to legend values. See section legend
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
tooltip	variable of data containing text or HTML to render as a tooltip. Only works on sf objects.
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
line_width_units	The units of the line width, one of 'meters', 'pixels'. When zooming in and out, meter sizes scale with the base map, and pixel sizes remain the same on screen.
line_width_scale	The line width multiplier that multiplied to all lines, including the LineString and MultiLineString features and also the outline for Polygon and MultiPolygon features if the stroked attribute is true
line_width_min_pixels	The minimum line width in pixels.
elevation_scale	Elevation multiplier. The final elevation is calculated by <code>elevationScale * getElevation(d)</code> . <code>elevationScale</code> is a handy property to scale all polygon elevation without updating the data
point_radius_scale	A global radius multiplier for all points.
point_radius_min_pixels	The minimum radius in pixels.
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
...	<code>clear_legend</code> and <code>clear_view</code> arguments passed to 'clear_()' functions

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for geojson

`list(fill_colour = 0, stroke_colour = 0, stroke_width = 0, elevation = 0, radius = 0)`

Raw Geojson

If using a GeoJSON string, and you **do not** supply one of the colouring arguments, the function will look for these fields inside the `properties` field of the Geojson

fill_colour

- `fill_colour`
- `fillColour`
- `fill_color`
- `fillColor`
- `fill`

stroke_colour

- `stroke_colour`
- `strokeColour`
- `stroke_color`
- `strokeColor`
- `stroke`
- `line_colour`
- `lineColour`
- `line_color`
- `lineColor`
- `line`

stroke_width

- `stroke_width`
- `strokeWdith`
- `line_width`
- `lineWidth`
- `width`
- `elevation`
- `radius`

These colour values should be valid hex-colour strings.

If you **do** provide values for the colouring arguments, the function will assume you want to use specific fields in the geojson for colouring. However, if you only supply a `fill_colour` value, the function will not automatically detect the `stroke_colour` (and vice versa)

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The `legend_options` can be used to control the appearance of the legend. This should be a named list, where the names are one of

- `css` - a string of valid css for controlling the appearance of the legend
- `title` - a string to use for the title of the legend
- `digits` - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The `legend_format` can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- `fill_colour`
- `stroke_colour`

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

## Not supplying colouring arguments, the function will try and find them in the GeoJSON
mapdeck(
  , location = c(145, -37.9)
  , zoom = 8
  , style = mapdeck_style("dark")
  , pitch = 35
) %>%
  add_geojson(
    data = geojson
    , auto_highlight = TRUE
  )

## only supplying values to use for fill, the stroke will be default
mapdeck(
  , location = c(145, -37.9)
  , zoom = 8
  , style = mapdeck_style("dark")
  , pitch = 35
) %>%
  add_geojson(
    data = geojson
    , fill_colour = "random"
  )

mapdeck(
```

```

, location = c(145, -37.9)
, zoom = 8
, style = mapdeck_style("dark")
, pitch = 35
) %>%
add_geojson(
  data = geojson
  , fill_colour = "random"
  , stroke_colour = "random"
)

mapdeck(
  , location = c(145, -37.9)
  , zoom = 8
  , style = mapdeck_style("dark")
  , pitch = 35
) %>%
add_geojson(
  data = geojson
  , fill_colour = "random"
  , stroke_colour = "random"
  , elevation = 300
)

## putting elevation and width values onto raw GeoJSON
library(geojsonsf)
sf <- geojsonsf::geojson_sf( geojson )
sf$width <- sample(1:100, size = nrow(sf), replace = TRUE)
sf$elevation <- sample(100:1000, size = nrow(sf), replace = TRUE)
geo <- geojsonsf::sf_geojson( sf )

mapdeck(
  , location = c(145, -37.9)
  , zoom = 8
  , style = mapdeck_style("dark")
  , pitch = 35
) %>%
add_geojson(
  data = geo
  , extruded = TRUE ## required to show elevated polygons
)

```

Description

Renders flat arcs along the great circle joining pairs of source and target points, specified as longitude/latitude coordinates.

Usage

```
add_greatcircle(
  map,
  data = get_map_data(map),
  layer_id = NULL,
  origin,
  destination,
  id = NULL,
  stroke_from = NULL,
  stroke_from_opacity = NULL,
  stroke_to = NULL,
  stroke_to_opacity = NULL,
  stroke_width = NULL,
  wrap_longitude = FALSE,
  tooltip = NULL,
  auto_highlight = FALSE,
  highlight_colour = "#AAFFFFFF",
  legend = F,
  legend_options = NULL,
  legend_format = NULL,
  palette = "viridis",
  na_colour = "#808080FF",
  update_view = TRUE,
  focus_layer = FALSE,
  transitions = NULL,
  digits = 6,
  brush_radius = NULL,
  ...
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
origin	vector of longitude and latitude columns, and optionally an elevation column, or an sfc column
destination	vector of longitude and latitude columns, and optionally an elevatino column, or an sfc column

<code>id</code>	an id value in data to identify layers when interacting in Shiny apps.
<code>stroke_from</code>	column of data or hex colour to use as the starting stroke colour. If using a hex colour, use either a single value, or a column of hex colours on data
<code>stroke_from_opacity</code>	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
<code>stroke_to</code>	column of data or hex colour to use as the ending stroke colour. If using a hex colour, use either a single value, or a column of hex colours on data
<code>stroke_to_opacity</code>	Either a string specifying the column of data containing the stroke opacity of each shape, or a value between 1 and 255 to be applied to all the shapes. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
<code>stroke_width</code>	width of the stroke in pixels
<code>wrap_longitude</code>	logical, whether to automatically wrap longitudes over the 180th antimeridian.
<code>tooltip</code>	variable of data containing text or HTML to render as a tooltip
<code>auto_highlight</code>	logical indicating if the shape under the mouse should auto-highlight
<code>highlight_colour</code>	hex string colour to use for highlighting. Must contain the alpha component.
<code>legend</code>	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
<code>legend_options</code>	A list of options for controlling the legend.
<code>legend_format</code>	A list containing functions to apply to legend values. See section legend
<code>palette</code>	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
<code>na_colour</code>	hex string colour to use for NA values
<code>update_view</code>	logical indicating if the map should update the bounds to include this layer
<code>focus_layer</code>	logical indicating if the map should update the bounds to only include this layer
<code>transitions</code>	list specifying the duration of transitions.
<code>digits</code>	number of digits for rounding coordinates
<code>brush_radius</code>	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
<code>...</code>	<code>clear_legend</code> and <code>clear_view</code> arguments passed to <code>'clear_()'</code> functions

Details

add_greatcircle supports POINT sf objects

MULTIPOINT objects will be treated as single points. That is, if an sf object has one row with a MULTIPOINT object consisting of two points, this will be expanded to two rows of single POINTs. Therefore, if the origin is a MULTIPOINT of two points, and the destination is a single POINT, the code will error as there will be an uneven number of rows

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
set_token("MAPBOX_TOKEN")

url <- 'https://raw.githubusercontent.com/plotly/datasets/master/2011_february_aa_flight_paths.csv'
flights <- read.csv(url)
flights$id <- seq_len(nrow(flights))
flights$stroke <- sample(1:3, size = nrow(flights), replace = TRUE)
flights$info <- paste0("<b>", flights$airport1, " - ", flights$airport2, "</b>")

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
  add_greatcircle(
    data = flights
```

```

    , layer_id = "greatcircle_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
    , tooltip = "info"
    , auto_highlight = TRUE
    , legend = TRUE
    , legend_options = list(
      stroke_from = list( title = "Origin airport" ),
      css = "max-height: 100px;")
  )

mapdeck( style = mapdeck_style("dark")) %>%
  add_greatcircle(
    data = flights
    , layer_id = "greatcircle_layer"
    , origin = c("start_lon", "start_lat")
    , destination = c("end_lon", "end_lat")
    , stroke_from = "airport1"
    , stroke_to = "airport2"
    , stroke_width = "stroke"
  )

## Using a 2-sfc-column sf object
library(sfheaders)

sf_flights <- sfheaders::sf_point( flights, x = "start_lon", y = "start_lat", keep = TRUE )
destination <- sfheaders::sfc_point( flights, x = "end_lon", y = "end_lat" )

sf_flights$destination <- destination

mapdeck() %>%
  add_greatcircle(
    data = sf_flights
    , origin = 'geometry'
    , destination = 'destination'
    , layer_id = 'greatcircles'
    , stroke_from = "airport1"
    , stroke_to = "airport2"
  )

```

Description

The Grid Layer renders a grid heatmap based on an array of points. It takes the constant size all each cell, projects points into cells. The color and height of the cell is scaled by number of points it contains.

Usage

```
add_grid(
  map,
  data = get_map_data(map),
  lon = NULL,
  lat = NULL,
  polyline = NULL,
  cell_size = 1000,
  extruded = TRUE,
  elevation = NULL,
  elevation_function = c("sum", "mean", "min", "max"),
  colour = NULL,
  colour_function = c("sum", "mean", "min", "max"),
  elevation_scale = 1,
  colour_range = NULL,
  legend = FALSE,
  legend_options = NULL,
  auto_highlight = FALSE,
  highlight_colour = "#AAFFFFFF",
  layer_id = NULL,
  update_view = TRUE,
  focus_layer = FALSE,
  digits = 6,
  transitions = NULL,
  brush_radius = NULL,
  ...
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
lon	column containing longitude values
lat	column containing latitude values
polyline	optional column of data containing the polylines, if using encoded polylines
cell_size	size of each cell in meters. Default 1000
extruded	logical indicating if cells are elevated or not. Default TRUE
elevation	the height the polygon extrudes from the map. Only available if neither stroke_colour or stroke_width are supplied. Default 0

elevation_function	one of 'min', 'mean', 'max', 'sum'. IF supplied it specifies how the elevation values are calculated. Defaults to sum.
colour	column containing numeric values to colour by.
colour_function	one of 'min', 'mean', 'max', 'sum'. If supplied it specifies how the colour values are calculated. Defaults to sum.
elevation_scale	elevation multiplier.
colour_range	vector of 6 hex colours
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear()' functions

Details

add_grid supports POINT and MULTIPOINT sf objects

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

See Also

add_hexagon

Examples

```

## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

df <- read.csv(paste0(
  'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/',
  'examples/3d-heatmap/heatmap-data.csv'
))

df <- df[ !is.na(df$lng ), ]

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_grid(
  data = df
  , lat = "lat"
  , lon = "lng"
  , cell_size = 5000
  , elevation_scale = 50
  , layer_id = "grid_layer"
  , auto_highlight = TRUE
)

## using sf object
library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lng", y = "lat")

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_grid(
  data = sf
  , cell_size = 5000
  , elevation_scale = 50
  , layer_id = "grid_layer"
  , auto_highlight = TRUE
)

## using colour and elevation functions, and legends
df$val <- sample(1:10, size = nrow(df), replace = TRUE)

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%
add_grid(
  data = df
  , lat = "lat"
  , lon = "lng"
  , layer_id = "hex_layer"
  , elevation_scale = 100
  , legend = TRUE
  , colour_function = "max"
  , colour = "val"
)

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%

```

```
add_grid(  
  data = df  
  , lat = "lat"  
  , lon = "lng"  
  , layer_id = "hex_layer"  
  , elevation_scale = 10  
  , legend = TRUE  
  , elevation_function = "mean"  
  , elevation = "val"  
)
```

add_h3

Add h3

Description

The h3 layer renders hexagons from the H3 geospatial indexing system. To use this layer you must specify `libraries = "h3"` within the `mapdeck()` call. See examples.

Usage

```
add_h3(  
  map,  
  data = get_map_data(map),  
  hexagon = NULL,  
  stroke_colour = NULL,  
  stroke_width = NULL,  
  stroke_opacity = NULL,  
  fill_colour = NULL,  
  fill_opacity = NULL,  
  elevation = NULL,  
  tooltip = NULL,  
  auto_highlight = FALSE,  
  elevation_scale = 1,  
  highlight_colour = "#AAFFFFFF",  
  light_settings = list(),  
  layer_id = NULL,  
  id = NULL,  
  palette = "viridis",  
  na_colour = "#808080FF",  
  legend = FALSE,  
  legend_options = NULL,  
  legend_format = NULL,  
  update_view = TRUE,  
  focus_layer = FALSE,
```

```

    transitions = NULL
  )

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
hexagon	column of data containing the hexagon indexes
stroke_colour	variable of data or hex colour for the stroke. If used, elevation is ignored. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_width	width of the stroke in meters. If used, elevation is ignored. Default 1.
stroke_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
fill_colour	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
elevation	the height the polygon extrudes from the map. Only available if neither stroke_colour or stroke_width are supplied. Default 0
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
elevation_scale	elevation multiplier.
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
light_settings	list of light setting parameters. See light_settings
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.

legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
transitions	list specifying the duration of transitions.

Details

add_h3 supports a data.frame with a column of h3 indexes

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for h3

```
list( elevation = 0 colour = 0 )
```

Examples

```
## Not run:

## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

mapdeck(
  style = mapdeck_style("dark")
  , location = c(0, 51.3)
  , zoom = 10
  , pitch = 60
  , libraries = "h3"
) %>%
add_h3(
  data = road_safety
  , hexagon = "hex"
  , fill_colour = "count"
  , auto_highlight = TRUE
  , legend = TRUE
  , elevation = "count"
  , elevation_scale = 20
  , palette = colourvalues::get_palette("inferno")
)

## End(Not run)
```

 add_heatmap

Add Heatmap

Description

The Heatmap Layer can be used to visualise spatial distribution of data. It implements Gaussian Kernel Density Estimation to render the heatmaps.

Usage

```
add_heatmap(
  map,
  data = get_map_data(map),
  lon = NULL,
  lat = NULL,
  polyline = NULL,
  weight = NULL,
  colour_range = NULL,
  radius_pixels = 30,
  intensity = 1,
  threshold = 0.05,
  layer_id = NULL,
  update_view = TRUE,
  focus_layer = FALSE,
  digits = 6,
  transitions = NULL,
  ...
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
lon	column containing longitude values
lat	column containing latitude values
polyline	optional column of data containing the polylines, if using encoded polylines
weight	the weight of each value. Default 1
colour_range	vector of 6 hex colours
radius_pixels	Radius of the circle in pixels, to which the weight of an object is distributed
intensity	Value that is multiplied with the total weight at a pixel to obtain the final weight. A value larger than 1 biases the output color towards the higher end of the spectrum, and a value less than 1 biases the output color towards the lower end of the spectrum

threshold	The HeatmapLayer reduces the opacity of the pixels with relatively low weight to create a fading effect at the edge. A larger threshold smoothens the boundaries of color blobs, while making pixels with low relative weight harder to spot (due to low alpha value). Threshold is defined as the ratio of the fading weight to the max weight, between 0 and 1. For example, 0.1 affects all pixels with weight under 10% of the max.
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_heatmap supports POINT and MULTIPOINT sf objects

note

The current version of this layer is supported only for WebGL2 enabled browsers So you may find it doesn't render in the RStudio viewer.

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for heatmap

```
list( intensity = 0, threshold = 0, radius_pixels = 0 )
```

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )
```

```

df <- read.csv(paste0(
  'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/',
  'examples/3d-heatmap/heatmap-data.csv'
))

df <- df[ !is.na(df$lng), ]
df$weight <- sample(1:10, size = nrow(df), replace = TRUE)

mapdeck( style = mapdeck_style('dark'), pitch = 45 ) %>%
  add_heatmap(
    data = df
    , lat = "lat"
    , lon = "lng"
    , weight = "weight",
    , layer_id = "heatmap_layer"
  )

## as an sf object
library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lng", y = "lat")

mapdeck( style = mapdeck_style('dark'), pitch = 45 ) %>%
  add_heatmap(
    data = sf
    , weight = "weight",
    , layer_id = "heatmap_layer"
  )

```

add_hexagon

Add hexagon

Description

The Hexagon Layer renders a hexagon heatmap based on an array of points. It takes the radius of hexagon bin, projects points into hexagon bins. The color and height of the hexagon is scaled by number of points it contains.

Usage

```

add_hexagon(
  map,
  data = get_map_data(map),
  polyline = NULL,
  lon = NULL,
  lat = NULL,
  layer_id = NULL,

```



```

radius = 1000,
elevation = NULL,
elevation_function = c("sum", "mean", "min", "max"),
colour = NULL,
colour_function = c("sum", "mean", "min", "max"),
legend = FALSE,
legend_options = NULL,
elevation_scale = 1,
auto_highlight = FALSE,
highlight_colour = "#AAFFFFFF",
colour_range = NULL,
update_view = TRUE,
focus_layer = FALSE,
digits = 6,
transitions = NULL,
brush_radius = NULL,
...
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
polyline	column of data containing the polylines
lon	column containing longitude values
lat	column containing latitude values
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
radius	in metres. Default 1000
elevation	column containing the elevation of the value.
elevation_function	one of 'min', 'mean', 'max', 'sum'. IF supplied it specifies how the elevation values are calculated. Defaults to sum.
colour	column containing numeric values to colour by.
colour_function	one of 'min', 'mean', 'max', 'sum'. If supplied it specifies how the colour values are calculated. Defaults to sum.
legend	logical indicating if a legend should be displayed
legend_options	A list of options for controlling the legend.
elevation_scale	value to scale the elevations of the hexagons. Default 1
auto_highlight	logical indicating if the shape under the mouse should auto-highlight

highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
colour_range	vector of 6 hex colours
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_hexagon supports POINT and MULTIPOINT sf objects

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for hexagon

```
list( elevation = 0 colour = 0 )
```

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

Examples

```
## Not run:

## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

df <- read.csv(paste0(
  'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/examples/'
  , '3d-heatmap/heatmap-data.csv'
))

df <- df[!is.na(df$lng), ]

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%
```

```

add_hexagon(
  data = df
  , lat = "lat"
  , lon = "lng"
  , layer_id = "hex_layer"
  , elevation_scale = 100
)

library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lng", y = "lat" )

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_hexagon(
  data = sf
  , layer_id = "hex_layer"
  , elevation_scale = 100
)

## Using elevation and colour
df$colour <- rnorm(nrow(df))
df$elevation <- rnorm(nrow(df))

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%
add_hexagon(
  data = df
  , lat = "lat"
  , lon = "lng"
  , layer_id = "hex_layer"
  , elevation_scale = 100
  , elevation = "weight"
  , colour = "colour"
)

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%
add_hexagon(
  data = df
  , lat = "lat"
  , lon = "lng"
  , layer_id = "hex_layer"
  , elevation_scale = 100
  , elevation = "weight"
  , elevation_function = "mean"
  , colour = "colour"
  , colour_function = "mean"
)

## with a legend
df$val <- sample(1:10, size = nrow(df), replace = TRUE)

mapdeck( style = mapdeck_style("dark"), pitch = 45) %>%
add_hexagon(
  data = df
  , lat = "lat"

```

```

, lon = "lng"
, layer_id = "hex_layer"
, elevation_scale = 100
, legend = TRUE
, legend_options = list( digits = 0 )
, colour_function = "mean"
, colour = "val"
)

## End(Not run)

```

add_i3s

Add I3S

Description

Adds OGC Indexed 3D Scene (I3S) tiles to the map. This layer is experimental.

Usage

```
add_i3s(map, data, layer_id = NULL)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly

Examples

```

## San Francisco buildings
i3s <- paste0(
  'https://tiles.arcgis.com/tiles/z2tnIkrLQ2BRzr6P/arcgis/rest/services/'
  , 'SanFrancisco_Bldgs/SceneServer/layers/0'
)

mapdeck(
  location = c(-122.41, 37.77)
  , zoom = 16
  , pitch = 60
) %>%
  add_i3s(
    data = i3s

```

```
)
```

```
add_line
```

```
Add line
```

Description

The Line Layer renders raised lines joining pairs of source and target coordinates

Usage

```
add_line(
  map,
  data = get_map_data(map),
  layer_id = NULL,
  origin,
  destination,
  id = NULL,
  stroke_colour = NULL,
  stroke_width = NULL,
  stroke_opacity = NULL,
  tooltip = NULL,
  auto_highlight = FALSE,
  highlight_colour = "#AAFFFFFF",
  palette = "viridis",
  na_colour = "#808080FF",
  legend = FALSE,
  legend_options = NULL,
  legend_format = NULL,
  update_view = TRUE,
  focus_layer = FALSE,
  digits = 6,
  transitions = NULL,
  brush_radius = NULL,
  ...
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly

origin	vector of longitude and latitude columns, and optionally an elevation column, or an sfc column
destination	vector of longitude and latitude columns, and optionally an elevation column, or an sfc column
id	an id value in data to identify layers when interacting in Shiny apps.
stroke_colour	variable or hex colour to use as the ending stroke colour.
stroke_width	width of the line in metres
stroke_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	<code>clear_legend</code> and <code>clear_view</code> arguments passed to <code>'clear_()'</code> functions

Details

`add_line` supports POINT sf objects

MULTIPOINT objects will be treated as single points. That is, if an sf object has one row with a MULTIPOINT object consisting of two points, this will be expanded to two rows of single POINTs. Therefore, if the origin is a MULTIPOINT of two points, and the destination is a single POINT, the code will error as there will be an uneven number of rows

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for line

```
list( origin = 0, destination = 0, stroke_colour = 0, stroke_width = 0 )
```

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

url <- 'https://raw.githubusercontent.com/plotly/datasets/master/2011_february_aa_flight_paths.csv'
flights <- read.csv(url)
flights$id <- seq_len(nrow(flights))
flights$stroke <- sample(1:3, size = nrow(flights), replace = TRUE)

mapdeck(style = mapdeck_style("dark"), pitch = 45 ) %>%
```

```

add_line(
  data = flights
  , layer_id = "line_layer"
  , origin = c("start_lon", "start_lat")
  , destination = c("end_lon", "end_lat")
  , stroke_colour = "airport1"
  , stroke_width = "stroke"
  , auto_highlight = TRUE
)

## Using a 2-sfc-column sf object
library(sfheaders)

sf_flights <- sfheaders::sf_point( flights, x = "start_lon", y = "start_lat", keep = TRUE )
destination <- sfheaders::sfc_point( flights, x = "end_lon", y = "end_lat" )

sf_flights$destination <- destination

mapdeck() %>%
  add_line(
    data = sf_flights
    , origin = 'geometry'
    , destination = 'destination'
    , layer_id = 'arcs'
    , stroke_colour = "airport1"
  )

```

add_mesh

Add Mesh

Description

Adds polygons to the map from a mesh3d object

Usage

```

add_mesh(
  map,
  data = get_map_data(map),
  fill_opacity = NULL,
  elevation = NULL,
  tooltip = NULL,
  auto_highlight = FALSE,
  highlight_colour = "#AAFFFFFF",
  light_settings = list(),
  layer_id = NULL,
  id = NULL,

```



```

palette = "viridis",
na_colour = "#808080FF",
legend = FALSE,
legend_options = NULL,
legend_format = NULL,
update_view = TRUE,
focus_layer = FALSE,
digits = 6,
transitions = NULL,
brush_radius = NULL
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
elevation	the height the polygon extrudes from the map. Only available if neither stroke_colour or stroke_width are supplied. Default 0
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
light_settings	list of light setting parameters. See light_settings
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of colourvalues::colour_palettes(). A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. list(fill_colour = "viridis", stroke_colour = "inferno")
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer

digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed

Details

add_mesh supports mesh3d objects

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

Examples

```
## exaggerate the elevation slightly
m <- melbourne_mesh
m$vb[3, ] <- m$vb[3, ] * 50

mapdeck() %>%
  add_mesh(
    data = m
  )
```

add_path	<i>Add Path</i>
----------	-----------------

Description

The Path Layer takes in lists of coordinate points and renders them as extruded lines with mitering.

Usage

```
add_path(  
  map,  
  data = get_map_data(map),  
  polyline = NULL,  
  stroke_colour = NULL,  
  stroke_width = NULL,  
  stroke_opacity = NULL,  
  dash_size = NULL,  
  dash_gap = NULL,  
  offset = NULL,  
  width_units = c("meters", "common", "pixels"),  
  width_min_pixels = NULL,  
  width_max_pixels = NULL,  
  width_scale = 1,  
  tooltip = NULL,  
  billboard = FALSE,  
  layer_id = NULL,  
  id = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  palette = "viridis",  
  na_colour = "#808080FF",  
  legend = FALSE,  
  legend_options = NULL,  
  legend_format = NULL,  
  update_view = TRUE,  
  focus_layer = FALSE,  
  digits = 6,  
  transitions = NULL,  
  brush_radius = NULL,  
  ...  
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system

polyline	optional column of data containing the polylines, if using encoded polylines
stroke_colour	variable of data or hex colour for the stroke. If used, elevation is ignored. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_width	width of the stroke in meters. Default 1.
stroke_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
dash_size	size of each dash, relative to the width of the stroke
dash_gap	size of the gap between dashes, relative to the width of the stroke
offset	The offset to draw each path with, relative to the width of the path. Negative offset is to the left hand side, and positive offset is to the right hand side. 0 extrudes the path so that it is centered at the specified coordinates.
width_units	The units of the line width, one of 'meters', 'common' or 'pixels'. When zooming in and out, meter sizes scale with the base map, and pixel sizes remain the same on screen.
width_min_pixels	The minimum path width in pixels. This can be used to prevent the path from getting too thin when zoomed out.
width_max_pixels	The maximum path width in pixels. This prop can be used to prevent the path from getting too thick when zoomed in.
width_scale	The path width multiplier that multiplied to all paths.
tooltip	variable of data containing text or HTML to render as a tooltip
billboard	logical indicating if the path always faces the camera (TRUE) or if it always faces up (FALSE)
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend

update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_path supports LINESTRING and MULTILINESTRING sf objects

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for path

```
list( path = 0, stroke_colour = 0, stroke_width = 0 )
```

gradient fill

If a colour is supplied for each coordinate (see examples), the colour along each segment of the line is gradient-filled. However, if either dash_gap, dash_size or offset are supplied the segment is filled with a solid colour, according to the first point on the segment.

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where 'map' is the map_id supplied to `mapdeckOutput()`, and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

mapdeck(
  style = mapdeck_style("dark")
) %>%
add_path(
  data = roads
  , stroke_colour = "RIGHT_LOC"
  , stroke_width = 20
  , layer_id = "path_layer"
  , tooltip = "ROAD_NAME"
  , auto_highlight = TRUE
  , legend = TRUE
)

## Dashed lines
mapdeck(
  style = mapdeck_style("dark")
) %>%
add_path(
  data = roads
  , stroke_colour = "RIGHT_LOC"
  , layer_id = "path_layer"
  , tooltip = "ROAD_NAME"
  , stroke_width = 1
  , dash_size = 0.5
  , dash_gap = 5
)

## Different dashes per path

sf <- mapdeck::roads
sf$dash_size <- sample(1:5, size = nrow( sf ), replace = TRUE )
```

```

sf$dash_gap <- sample(1:5, size = nrow( sf ), replace = TRUE )

mapdeck(
  style = mapdeck_style("dark")
) %>%
add_path(
  data = sf
  , stroke_colour = "RIGHT_LOC"
  , layer_id = "path_layer"
  , tooltip = "ROAD_NAME"
  , dash_size = "dash_size"
  , dash_gap = "dash_gap"
)

## Offset lines
sf <- mapdeck::roads
sf$offset <- sample(-10:10, size = nrow( sf ), replace = TRUE )

mapdeck(
  style = mapdeck_style("light")
) %>%
add_path(
  data = sf
  , stroke_colour = "ROAD_NAME"
  , offset = "offset"
)

## Multi Coloured line
## You need to supply one colour per coordinate in the sf object
sf_line <- sfheaders::sf_linestring(
  obj = data.frame(
    id = c(1,1,1,1,1,2,2,2,2)
    , x = c(0,0,1,1,2,-1,-1,0,0,1)
    , y = c(0,1,1,2,2,0,1,1,2,2)
    , col = c(1,2,3,4,5,5,4,3,2,1)
  )
  , x = "x"
  , y = "y"
  , linestring_id = "id"
  , list_columns = "col"
  , keep = TRUE
)

mapdeck(
  style = mapdeck_style("light")
) %>%
add_path(
  data = sf_line
  , stroke_colour = "col"
  , stroke_width = 50000
)

## If using dashed lines, colours won't be gradient-filled

```

```
mapdeck(  
  style = mapdeck_style("light")  
) %>%  
  add_path(  
    data = sf_line  
    , stroke_colour = "col"  
    , stroke_width = 500  
    , dash_size = 10  
    , dash_gap = 10  
  )
```

add_pointcloud

Add Pointcloud

Description

The Pointcloud Layer takes in coordinate points and renders them as circles with a certain radius.

Usage

```
add_pointcloud(  
  map,  
  data = get_map_data(map),  
  lon = NULL,  
  lat = NULL,  
  elevation = NULL,  
  polyline = NULL,  
  radius = 10,  
  fill_colour = NULL,  
  fill_opacity = NULL,  
  tooltip = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  light_settings = list(),  
  layer_id = NULL,  
  id = NULL,  
  palette = "viridis",  
  na_colour = "#808080FF",  
  legend = FALSE,  
  legend_options = NULL,  
  legend_format = NULL,  
  update_view = TRUE,  
  focus_layer = FALSE,  
  digits = 6,
```



```

    transitions = NULL,
    brush_radius = NULL,
    ...
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
lon	column containing longitude values
lat	column containing latitude values
elevation	column containing the elevation values. Default 0
polyline	optional column of data containing the polylines, if using encoded polylines
radius	value in pixels of each point. Default 10.
fill_colour	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
light_settings	list of light setting parameters. See light_settings
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer

digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_pointcloud supports POINT and MULTIPOINT sf objects

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for pointcloud

```
list( position = 0, fill_colour = 0 )
```

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where 'map' is the map_id supplied to `mapdeckOutput()`, and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

df <- capitals
df$z <- sample(10000:10000000, size = nrow(df))

mapdeck(style = mapdeck_style("dark")) %>%
  add_pointcloud(
    data = df
    , lon = 'lon'
    , lat = 'lat'
    , elevation = 'z'
    , layer_id = 'point'
    , fill_colour = "country"
    , tooltip = "country"
  )

## as an sf object with a Z attribute
library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lon", y = "lat", z = "z" )

mapdeck(style = mapdeck_style("dark")) %>%
  add_pointcloud(
    data = sf
    , layer_id = 'point'
    , fill_colour = "country"
    , tooltip = "country"
    , update_view = FALSE
  )
```

`add_polygon`*Add Polygon*

Description

The Polygon Layer renders filled and/or stroked polygons.

Usage

```

add_polygon(
  map,
  data = get_map_data(map),
  polyline = NULL,
  stroke_colour = NULL,
  stroke_width = NULL,
  stroke_opacity = NULL,
  fill_colour = NULL,
  fill_opacity = NULL,
  elevation = NULL,
  tooltip = NULL,
  auto_highlight = FALSE,
  elevation_scale = 1,
  highlight_colour = "#AAFFFFFF",
  light_settings = list(),
  layer_id = NULL,
  id = NULL,
  palette = "viridis",
  na_colour = "#808080FF",
  legend = FALSE,
  legend_options = NULL,
  legend_format = NULL,
  update_view = TRUE,
  focus_layer = FALSE,
  digits = 6,
  transitions = NULL,
  brush_radius = NULL,
  ...
)

```

Arguments

<code>map</code>	a mapdeck map object
<code>data</code>	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
<code>polyline</code>	optional column of data containing the polylines, if using encoded polylines
<code>stroke_colour</code>	variable of data or hex colour for the stroke. If used, <code>elevation</code> is ignored. If using a hex colour, use either a single value, or a column of hex colours on data
<code>stroke_width</code>	width of the stroke in meters. If used, <code>elevation</code> is ignored. Default 1.
<code>stroke_opacity</code>	Either a string specifying the column of data containing the opacity of each shape, or a single value in $[0,255]$, or $[0, 1)$, to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
<code>fill_colour</code>	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data

fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
elevation	the height the polygon extrudes from the map. Only available if neither stroke_colour or stroke_width are supplied. Default 0
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
elevation_scale	elevation multiplier.
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
light_settings	list of light setting parameters. See light_settings
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of colourvalues::colour_palettes(). A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. list(fill_colour = "viridis", stroke_colour = "inferno")
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_polygon supports POLYGON and MULTIPOLYGON sf objects

data

If the data is a simple feature object, the geometry column is automatically detected. If the object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for polygon

```
list( polygon = 0, fill_colour = 0, stroke_colour = 0, stroke_width = 0, elevation = 0 )
```

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

library(geojsonsf)

sf <- geojsonsf::geojson_sf("https://symbolixau.github.io/data/geojson/SA2_2016_VIC.json")

mapdeck(
  style = mapdeck_style('dark')
```

```

) %>%
  add_polygon(
    data = sf
    , layer = "polygon_layer"
    , fill_colour = "SA2_NAME16"
  )

df <- melbourne ## data.frame with encoded polylines
df$elevation <- sample(100:5000, size = nrow(df))
df$info <- paste0("<b>SA2 - </b><br>",df$SA2_NAME)

mapdeck(
  style = mapdeck_style('dark')
  , location = c(145, -38)
  , zoom = 8
) %>%
  add_polygon(
    data = df
    , polyline = "geometry"
    , layer = "polygon_layer"
    , fill_colour = "SA2_NAME"
    , elevation = "elevation"
    , tooltip = 'info'
    , legend = TRUE
  )

```

add_scatterplot

Add Scatterplot

Description

The Scatterplot Layer takes in coordinate points and renders them as circles with a certain radius.

Usage

```

add_scatterplot(
  map,
  data = get_map_data(map),
  lon = NULL,
  lat = NULL,
  polyline = NULL,
  radius = NULL,
  radius_min_pixels = 1,
  radius_max_pixels = NULL,
  fill_colour = NULL,
  fill_opacity = NULL,

```

```

stroke_colour = NULL,
stroke_width = NULL,
stroke_opacity = NULL,
tooltip = NULL,
auto_highlight = FALSE,
highlight_colour = "#AAFFFFFF",
layer_id = NULL,
id = NULL,
palette = "viridis",
na_colour = "#808080FF",
legend = FALSE,
legend_options = NULL,
legend_format = NULL,
digits = 6,
update_view = TRUE,
focus_layer = FALSE,
transitions = NULL,
brush_radius = NULL,
collision_filter = FALSE,
...
)

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
lon	column containing longitude values
lat	column containing latitude values
polyline	optional column of data containing the polylines, if using encoded polylines
radius	in metres. Default 1
radius_min_pixels	the minimum radius in pixels. Can prevent circle from getting too small when zoomed out small for the given zoom level
radius_max_pixels	the maximum radius in pixels. Can prevent the circle from getting too big when zoomed in
fill_colour	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
stroke_colour	variable of data or hex colour for the stroke. If used, elevation is ignored. If using a hex colour, use either a single value, or a column of hex colours on data
stroke_width	width of the stroke in meters. If used, elevation is ignored. Default 1.

stroke_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
tooltip	variable of data containing text or HTML to render as a tooltip
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
digits	number of digits for rounding coordinates
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
collision_filter	set to 'TRUE' if you want to hide features that overlap other features. Default is 'FALSE'
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_scatterplot supports POINT and MULTIPOINT sf objects

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for scatterplot

`list(position = 0, fill_colour = 0, radius = 0)`

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

legend

The `legend_options` can be used to control the appearance of the legend. This should be a named list, where the names are one of

- `css` - a string of valid css for controlling the appearance of the legend
- `title` - a string to use for the title of the legend
- `digits` - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The `legend_format` can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- `fill_colour`
- `stroke_colour`

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The `id` is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where 'map' is the `map_id` supplied to `mapdeckOutput()`, and 'arc' is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
  add_scatterplot(
    data = capitals
    , lat = "lat"
    , lon = "lon"
    , radius = 100000
    , fill_colour = "country"
    , layer_id = "scatter_layer"
    , tooltip = "capital"
```

```

)

## using legend options
mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_scatterplot(
  data = capitals
  , lat = "lat"
  , lon = "lon"
  , radius = 100000
  , fill_colour = "lon"
  , stroke_colour = "lat"
  , layer_id = "scatter_layer"
  , tooltip = "capital"
  , legend = TRUE
  , legend_options = list( digits = 5 )
)

df <- read.csv(paste0(
'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/' ,
'examples/3d-heatmap/heatmap-data.csv'
))

df <- df[ !is.na(df$lng), ]

mapdeck(style = mapdeck_style("dark"), pitch = 45 ) %>%
add_scatterplot(
  data = df
  , lat = "lat"
  , lon = "lng"
  , layer_id = "scatter_layer"
  , stroke_colour = "lng"
)

## as an sf object
library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lng", y = "lat")

mapdeck( style = mapdeck_style("dark"), pitch = 45 ) %>%
add_scatterplot(
  data = sf
  , radius = 100
  , fill_colour = "country"
  , layer_id = "scatter_layer"
  , tooltip = "capital"
)

```

Description

The Screen Grid Layer takes in an array of latitude and longitude coordinated points, aggregates them into histogram bins and renders as a grid

Usage

```
add_screengrid(
  map,
  data = get_map_data(map),
  lon = NULL,
  lat = NULL,
  polyline = NULL,
  weight = NULL,
  aggregation = c("sum", "mean", "min", "max"),
  colour_range = NULL,
  opacity = 0.8,
  cell_size = 50,
  layer_id = NULL,
  update_view = TRUE,
  focus_layer = FALSE,
  digits = 6,
  ...
)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
lon	column containing longitude values
lat	column containing latitude values
polyline	optional column of data containing the polylines, if using encoded polylines
weight	the weight of each value. Default 1
aggregation	one of 'min', 'mean', 'max', 'sum'. If supplied it specifies how the weights used.
colour_range	vector of 6 hex colours
opacity	opacity of cells. Value between 0 and 1. Default 0.8
cell_size	size of grid squares in pixels. Default 50
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_screengrid supports POINT and MULTIPOINT sf objects

data

If the data is a simple feature object, the geometry column is automatically detected. If the sf object contains more than one geometry column and you want to use a specific one, you'll need to set the active geometry using `sf::st_geometry(x) <- "your_column"`, where "your_column" is the name of the column you're activating. See `?sf::st_geometry`

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

df <- read.csv(paste0(
  'https://raw.githubusercontent.com/uber-common/deck.gl-data/master/',
  'examples/3d-heatmap/heatmap-data.csv'
))

df <- df[ !is.na(df$lng), ]
df$weight <- sample(1:10, size = nrow(df), replace = TRUE)

mapdeck( style = mapdeck_style('dark'), pitch = 45 ) %>%
add_screengrid(
  data = df
  , lat = "lat"
  , lon = "lng"
  , weight = "weight",
  , layer_id = "screengrid_layer"
  , cell_size = 10
  , opacity = 0.3
)

## as an sf object
library(sfheaders)
sf <- sfheaders::sf_point( df, x = "lng", y = "lat")

mapdeck( style = mapdeck_style('dark'), pitch = 45 ) %>%
add_screengrid(
  data = sf
  , weight = "weight",
  , layer_id = "screengrid_layer"
  , cell_size = 10
  , opacity = 0.3
)
```

add_sf	<i>Add sf</i>
--------	---------------

Description

Adds an sf object to the map.

Usage

```
add_sf(map, data = get_map_data(map), ...)
```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
...	other arguments passed to one of the plotting layers. See details

Details

The plotting layer is determined by the type of sf geometries.

- POINT and MULTIPOINT objects will call [add_scatterplot](#)
- LINestring and MULTILINESTRING objects will call [add_path](#)
- POLYGON and MULTIPOLYGON objects will call [add_polygon](#)
- GEOMETRY objects will call [add_geojson](#)

add_terrain	<i>Add terrain</i>
-------------	--------------------

Description

Adds mesh surfaces from height map images

Usage

```
add_terrain(
  map,
  layer_id = NULL,
  elevation_data,
  texture = NULL,
  elevation_decoder = c(1, 0, 0, 0),
  bounds = NULL,
  max_error = 4,
  update_view = TRUE,
  focus_layer = FALSE
)
```

Arguments

map	a mapdeck map object
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
elevation_data	Image URL that encodes height data. When elevation_data is a URL template, i.e. a string containing '{x}' and '{y}', it loads terrain tiles on demand and renders a mesh for each tile. If elevation_data is an absolute URL, as in the example, a single mesh is used, and the bounds argument is required to position it into the world space.
texture	Image URL to use as the texture
elevation_decoder	Four value used to convert a pixel to elevation in metres. The values correspond to rScale, gScale, bScale, offset. See details
bounds	Four values (c(left, bottom, right, top)). bounds of the image to fit in x,y coordinates into. left and right refers to the world longitude/x at the corresponding side of the image. top and bottom refers to the world latitude/y at the corresponding side of the image. Must be supplied when using non-tiled elevation_data
max_error	Martini error tolerance in metres, smaller number results in more detailed mesh.
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer

Details

The elevation_decoder contains four values representing

- rScale - Multiplier of the red channel
- gScale - Multiplier of the green channel
- bScale - Multiplier of the blue channel
- offset - translation of the sum

Each colour channel is a number between [0, 255].

Examples

```
set_token( "MAPBOX_TOKEN" )
## Digital elevation model from https://www.usgs.gov/
elevation <- 'https://raw.githubusercontent.com/visgl/deck.gl-data/master/website/terrain.png'
texture <- 'https://raw.githubusercontent.com/visgl/deck.gl-data/master/website/terrain-mask.png'
bounds <- c(-122.5233, 37.6493, -122.3566, 37.8159)

mapdeck() %>%
  add_terrain(
    , elevation_data = elevation
    , elevation_decoder = c(1,0,0,0)
```

```
, texture = texture  
, bounds = bounds  
, max_error = 1  
)
```

add_text

Add Text

Description

The Text Layer renders text labels on the map

Usage

```
add_text(  
  map,  
  data = get_map_data(map),  
  text,  
  lon = NULL,  
  lat = NULL,  
  polyline = NULL,  
  fill_colour = NULL,  
  fill_opacity = NULL,  
  size = NULL,  
  angle = NULL,  
  anchor = NULL,  
  alignment_baseline = NULL,  
  billboard = TRUE,  
  font_family = "Monaco, monospace",  
  font_weight = "normal",  
  tooltip = NULL,  
  layer_id = NULL,  
  id = NULL,  
  auto_highlight = FALSE,  
  highlight_colour = "#AAFFFFFF",  
  palette = "viridis",  
  na_colour = "#808080FF",  
  legend = FALSE,  
  legend_options = NULL,  
  legend_format = NULL,  
  update_view = TRUE,  
  focus_layer = FALSE,  
  digits = 6,  
  transitions = NULL,  
  brush_radius = NULL,
```



```

    collision_filter = FALSE,
    ...
  )

```

Arguments

map	a mapdeck map object
data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
text	column of data containing the text. The data must be a character.
lon	column containing longitude values
lat	column containing latitude values
polyline	optional column of data containing the polylines, if using encoded polylines
fill_colour	column of data or hex colour for the fill colour. If using a hex colour, use either a single value, or a column of hex colours on data
fill_opacity	Either a string specifying the column of data containing the opacity of each shape, or a single value in [0,255], or [0, 1), to be applied to all the shapes. Default 255. If a hex-string is used as the colour, this argument is ignored and you should include the alpha on the hex string
size	column of data containing the size of the text. Default 32
angle	column of data containing the angle of the text. Default 0
anchor	column of data containing the anchor of the text. One of 'start', 'middle' or 'end'
alignment_baseline	column of data containing the alignment. One of 'top', 'center' or 'bottom'
billboard	logical indicating if the text always faces the camera (TRUE) or if it always faces up (FALSE)
font_family	specifies a prioritised list of one or more font family names and/or generic family names. Follow the specifics for CSS font-family https://developer.mozilla.org/en-US/docs/Web/CSS/font-family
font_weight	specifies the font weight. Follow the specifics for CSS font-weight https://htmldog.com/references/css/properties/font-weight/
tooltip	variable of data containing text or HTML to render as a tooltip
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly
id	an id value in data to identify layers when interacting in Shiny apps.
auto_highlight	logical indicating if the shape under the mouse should auto-highlight
highlight_colour	hex string colour to use for highlighting. Must contain the alpha component.
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>

na_colour	hex string colour to use for NA values
legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
transitions	list specifying the duration of transitions.
brush_radius	radius of the brush in metres. Default NULL. If supplied, the arcs will only show if the origin or destination are within the radius of the mouse. If NULL, all arcs are displayed
collision_filter	set to 'TRUE' if you want to hide features that overlap other features. Default is 'FALSE'
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_text supports POINT and MULTIPOINT sf objects

transitions

The transitions argument lets you specify the time it will take for the shapes to transition from one state to the next. Only works in an interactive environment (Shiny) and on WebGL-2 supported browsers and hardware.

The time is in milliseconds

Available transitions for text

```
list( position = 0, fill_colour = 0, angle = 0, size = 0 )
```

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour

- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The `id` is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use `observeEvent({input$map_arc_click})`, where `'map'` is the `map_id` supplied to `mapdeckOutput()`, and `'arc'` is the layer you are clicking on

Examples

```
## You need a valid access token from Mapbox
key <- 'abc'
set_token( key )

mapdeck(
  style = mapdeck_style('dark')
) %>%
  add_text(
    data = capitals
    , lon = 'lon'
    , lat = 'lat'
    , fill_colour = 'country'
    , text = 'capital'
    , layer_id = 'text'
  )
```

add_title

Add Title

Description

Adds a title to a map

Usage

```
add_title(map, title, layer_id = NULL)
```

Arguments

map	a mapdeck map object
title	Either a single string for the title, or a list with a 'title' element, and an optional 'css' element. See examples
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly

Examples

```
mapdeck() %>%
  add_title(title = "first title", layer_id = "first") %>%
  add_title(title = list(
    title = "second title",
    css = "background-color: red;"),
    layer_id = "second") %>%
  add_title(title = list(
    title = "Another title",
    css = "background-color: transparent;"),
    layer_id = "third")
```

 add_trips

Add Trips

Description

The Trips Layer takes an sf object with Z (elevation) and M (time) attributes and renders it as animated trips

Usage

```
add_trips(
  map,
  data = get_map_data(map),
  stroke_colour = NULL,
  stroke_width = NULL,
  width_units = c("meters", "pixels"),
  width_min_pixels = NULL,
  width_max_pixels = NULL,
  width_scale = 1,
  opacity = 0.3,
  palette = "viridis",
  trail_length = 180,
```

```

    start_time = get_m_range_start(data),
    end_time = get_m_range_end(data),
    animation_speed = 30,
    layer_id = NULL,
    legend = FALSE,
    legend_options = NULL,
    legend_format = NULL,
    update_view = TRUE,
    focus_layer = FALSE,
    digits = 6,
    ...
)

```

Arguments

map	a mapdeck map object
data	sf object with XYZM dimensions.
stroke_colour	variable of data or hex colour for the stroke.
stroke_width	width of the stroke in meters. Default 1.
width_units	The units of the line width, one of 'meters', 'common' or 'pixels'. When zooming in and out, meter sizes scale with the base map, and pixel sizes remain the same on screen.
width_min_pixels	The minimum path width in pixels. This can be used to prevent the path from getting too thin when zoomed out.
width_max_pixels	The maximum path width in pixels. his prop can be used to prevent the path from getting too thick when zoomed in.
width_scale	The path width multiplier that multiplied to all paths.
opacity	single value in [0,1]
palette	string or matrix. String will be one of <code>colourvalues::colour_palettes()</code> . A matrix must have at least 5 rows, and 3 or 4 columns of values between [0, 255], where the 4th column represents the alpha. You can use a named list to specify a different palette for different colour options (where available), e.g. <code>list(fill_colour = "viridis", stroke_colour = "inferno")</code>
trail_length	how long it takes for the trail to completely fade out (in same units as timestamps)
start_time	the minimum timestamp
end_time	the maximum timestamp
animation_speed	speed of animation
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly

legend	either a logical indicating if the legend(s) should be displayed, or a named list indicating which colour attributes should be included in the legend.
legend_options	A list of options for controlling the legend.
legend_format	A list containing functions to apply to legend values. See section legend
update_view	logical indicating if the map should update the bounds to include this layer
focus_layer	logical indicating if the map should update the bounds to only include this layer
digits	number of digits for rounding coordinates
...	clear_legend and clear_view arguments passed to 'clear_()' functions

Details

add_trips supports LINESTRING and MULTILINESTRING sf objects

legend

The legend_options can be used to control the appearance of the legend. This should be a named list, where the names are one of

- css - a string of valid css for controlling the appearance of the legend
- title - a string to use for the title of the legend
- digits - number to round the legend values to

If the layer allows different fill and stroke colours, you can use different options for each. See examples in [add_arc](#).

The legend_format can be used to control the format of the values in the legend. This should be a named list, where the names are one of

- fill_colour
- stroke_colour

depending on which type of colouring the layer supports.

The list elements must be functions to apply to the values in the legend.

id

The id is returned to your R session from an interactive shiny environment by observing layer clicks. This is useful for returning the data.frame row relating to the clicked shape.

From within a shiny server you would typically use observeEvent({input\$map_arc_click}), where 'map' is the map_id supplied to mapdeckOutput(), and 'arc' is the layer you are clicking on

Examples

```
set_token( "MAPBOX_TOKEN")
sf <- city_trail

mapdeck(
  style = mapdeck_style("dark")
```

```

) %>%
  add_trips(
    data = sf
    , animation_speed = 500
    , trail_length = 500
    , stroke_colour = "#FFFFFF"
    , stroke_width = 25
  )

## Multi-coloured trips
## requires a colour for each coordiante
## In this example I'm assining the elevation (z) value
## to a new column
df <- sfheaders::sf_to_df( city_trail )
df$colour <- df$z
sf <- sfheaders::sf_linestring(
  obj = df
  , x = "x"
  , y = "y"
  , z = "z"
  , m = "m"
  , keep = TRUE
  , list_column = "colour"
)

mapdeck(
  style = mapdeck_style("light")
) %>%
  add_trips(
    data = sf
    , animation_speed = 1000
    , trail_length = 1000
    , stroke_colour = "colour"
    , stroke_width = 50
    , legend = TRUE
  )

## New York Taxi Trips
json <- jsonify::from_json(
  "https://raw.githubusercontent.com/visgl/deck.gl-data/master/examples/trips/trips.json"
)

lens <- vapply( json$segments, nrow, 1L )
mat <- do.call( rbind, json$segments )
df <- setNames( as.data.frame( mat ), c("x","y","m") )
idx <- rep( seq_along( lens ), times = lens )
df$vendor <- rep( json$vendor, times = lens )

df$z <- 0 ## z column is required in SF object
df$idx <- idx

## Using the timestamp as a colour
df$timestamp <- df$m

```

```
sf_line <- sfheaders::sf_linestring(  
  obj = df  
  , x = "x"  
  , y = "y"  
  , z = "z"  
  , m = "m"  
  , linestring_id = "idx"  
  , keep = TRUE  
  , list_column = "timestamp"  
)  
  
mapdeck(  
  style = mapdeck_style("dark")  
) %>%  
  add_trips(  
    data = sf_line  
    , stroke_colour = "timestamp"  
    , animation_speed = 1000  
    , trail_length = 1000  
    , palette = colourvalues::get_palette("viridis")[100:256, ]  
  )
```

capitals

Capital cities for each country

Description

A data set containing the coordinates of 200 capital cities in the world

Usage

```
capitals
```

Format

A data frame with 200 observations and 4 variables

country country name

capital capital name

lat latitude of capital

lon longitude of capital

city_trail	<i>city_trail</i>
------------	-------------------

Description

An sf object of a cyclist cycling around Melbourne's Capital City Trail

Usage

```
city_trail
```

Format

An object of class sf (inherits from data.frame) with 1 rows and 3 columns.

clear_animated_arc	<i>Clear Animated Arc</i>
--------------------	---------------------------

Description

Clears elements from a map

Clears elements from a map

Usage

```
clear_animated_arc(map, layer_id = NULL, update_view = TRUE)
```

```
clear_line(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
```

```
clear_arc(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
```

```
clear_bitmap(map, layer_id = NULL, update_view = TRUE)
```

```
clear_column(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
```

```
clear_geojson(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
```

```
clear_greatcircle(  
  map,  
  layer_id = NULL,  
  update_view = TRUE,  
  clear_legend = TRUE  
)
```

```
clear_grid(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
```

```

clear_h3_hexagon(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_h3(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_heatmap(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_hexagon(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_line(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_mesh(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_path(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_pointcloud(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_polygon(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_scatterplot(
  map,
  layer_id = NULL,
  update_view = TRUE,
  clear_legend = TRUE
)
clear_screengrid(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_terrain(map, layer_id = NULL, update_view = TRUE)
clear_text(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)
clear_title(map, layer_id = NULL)
clear_trips(map, layer_id = NULL, update_view = TRUE, clear_legend = TRUE)

```

Arguments

<code>map</code>	a mapdeck map object
<code>layer_id</code>	the <code>layer_id</code> of the layer you want to clear
<code>update_view</code>	logical indicating if the map should update the bounds after removing the layer
<code>clear_legend</code>	logical indicating if the legend should be removed

`clear_legend`
Clear Legend

Description

Clears the legend for a given layer_id

Usage

clear_legend(map, layer_id)

Arguments

map	the map from which you want to clear the legend.
layer_id	single value specifying an id for the layer. Use this value to distinguish between shape layers of the same type. Layers with the same id are likely to conflict and not plot correctly

clear_tokens	<i>Clear tokens</i>
--------------	---------------------

Description

Clears the access tokens

Usage

clear_tokens()

geojson	<i>Geojson</i>
---------	----------------

Description

A GeoJSON object of polygons, lines and points in Melbourne

Usage

geojson

Format

a 'json' object

legend_element	<i>Legend Element</i>
----------------	-----------------------

Description

Creates a mapdeck legend element for when you want to manually specify a legend (using [mapdeck_legend](#))

Usage

```
legend_element(  
  variables,  
  colours,  
  colour_type = c("fill", "stroke"),  
  variable_type = c("category", "gradient"),  
  title = "",  
  css = ""  
)
```

Arguments

variables	variables assigned to colours
colours	vector of hex colours assigned to variables
colour_type	one of "fill" or "stroke"
variable_type	one of category (discrete) or gradient (continuous)
title	string used as the legend title
css	string of css to control appearance.

See Also

[mapdeck_legend](#)

Examples

```
l1 <- legend_element(  
  variables = c("a", "b")  
  , colours = c("#00FF00", "#FF0000")  
  , colour_type = "fill"  
  , variable_type = "category"  
  , title = "my title"  
)
```

light_settings	<i>Light Settings</i>
----------------	-----------------------

Description

List object containing light settings.

Details

Available in [add_geojson](#), [add_pointcloud](#) and [add_polygon](#)

- numberOfLights - the number of lights. Maximum of 5
- lightsPosition - vector of x, y, z coordinates. Must be 3x the number of lights
- ambientRatio - the ambient ratio of the lights

Examples

```
light <- list(  
  lightsPosition = c(-150, 75, 0)  
  , numberOfLights = 1  
  , ambientRatio = 0.2  
)
```

mapdeck	<i>mapdeck</i>
---------	----------------

Description

mapdeck

Usage

```
mapdeck(  
  data = NULL,  
  token = get_access_token(api = "mapbox"),  
  width = NULL,  
  height = NULL,  
  padding = 0,  
  style = "mapbox://styles/mapbox/streets-v9",  
  pitch = 0,  
  zoom = 0,  
  bearing = 0,  
  libraries = NULL,  
  max_zoom = 20,
```

```

    min_zoom = 0,
    max_pitch = 60,
    min_pitch = 0,
    location = c(0, 0),
    show_view_state = FALSE,
    repeat_view = FALSE
)

```

Arguments

data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
token	Mapbox Access token. Use <code>set_token()</code> or <code>Sys.setenv()</code> to set a global token. See Access Tokens section for further details. If left empty layers will still be plotted, but without a Mapbox map.
width	the width of the map
height	the height of the map
padding	the padding of the map
style	the style of the map (see mapdeck_style)
pitch	the pitch angle of the map
zoom	zoom level of the map
bearing	bearing of the map between 0 and 360
libraries	additional libraries required by some layers. Currently 'h3' is required for add_h3 .
max_zoom	sets the maximum zoom level
min_zoom	sets the minimum zoom level
max_pitch	sets the maximum pitch
min_pitch	sets the minimum pitch
location	unnamed vector of lon and lat coordinates (in that order)
show_view_state	logical, indicating whether to add the current View State to the map. When TRUE, the following is added as an overlay to the map <ul style="list-style-type: none"> • width • height • latitude & longitude • zoom • bearing • pitch • altitude • viewBounds • interactionState
repeat_view	Logical indicating if the layers should repeat at low zoom levels

Access Tokens

If the token argument is not used, the map will search for the token, firstly by checking if `set_token()` was used, then it will search environment variables using `Sys.getenv()` and the following values, in this order

```
c("MAPBOX_TOKEN", "MAPBOX_KEY", "MAPBOX_API_TOKEN", "MAPBOX_API_KEY",
  "MAPBOX", "MAPDECK")
```

If multiple tokens are found, the first one is used

 mapdeck-shiny

Shiny bindings for mapdeck

Description

Output and render functions for using mapdeck within Shiny applications and interactive Rmd documents.

Usage

```
mapdeckOutput(outputId, width = "100%", height = "400px")
```

```
renderMapdeck(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a mapdeck
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable.

 mapdeck_dependencies

Mapdeck Dependencies

Description

Adds the required mapdeck javascript dependencies to a Shiny UI when you want to use mapdeck layers, but not with a mapdeck map.

Usage

```
mapdeck_dependencies()
```

mapdeck_dispatch	<i>mapdeck dispatch</i>
------------------	-------------------------

Description

Extension points for plugins

Usage

```
mapdeck_dispatch(
  map,
  funcName,
  mapdeck = stop(paste(funcName, "requires a map update object")),
  mapdeck_update = stop(paste(funcName, "does not support map update objects"))
)

invoke_method(map, method, ...)
```

Arguments

map	a map object, as returned from mapdeck
funcName	the name of the function that the user called that caused this mapdeck_dispatch call; for error message purposes
mapdeck	an action to be performed if the map is from mapdeck
mapdeck_update	an action to be performed if the map is from mapdeck_update
method	the name of the JavaScript method to invoke
...	unnamed arguments to be passed to the JavaScript method

Value

mapdeck_dispatch returns the value of mapdeck or or an error. invokeMethod returns the map object that was passed in, possibly modified.

mapdeck_legend	<i>Mapdeck Legend</i>
----------------	-----------------------

Description

Constructs legend elements into the correct JSON format for plotting on the map

Usage

```
mapdeck_legend(legend_elements)
```


Arguments

legend_elements
vector of legend elements (made from [legend_element](#))

See Also

[legend_element](#)

Examples

```
l1 <- legend_element(  
  variables = c("a", "b")  
  , colours = c("#00FF00", "#FF0000")  
  , colour_type = "fill"  
  , variable_type = "category"  
  , title = "my title"  
)  
  
mapdeck_legend(l1)
```

mapdeck_style

Mapdeck Style

Description

Various styles available to all Mapbox accounts using a valid access token. Available styles are listed at <https://docs.mapbox.com/api/maps/#styles>.

Usage

```
mapdeck_style(  
  style = c("dark", "light", "outdoors", "streets", "satellite", "satellite-streets")  
)
```

Arguments

style one of streets, outdoors, light, dark, satellite, satellite-streets

Examples

```
## You need a valid access token from Mapbox  
key <- 'abc'  
  
## set a map style  
mapdeck(token = key, style = mapdeck_style("dark"))
```

mapdeck_tokens	<i>Mapdeck_tokens</i>
----------------	-----------------------

Description

Retrieves the mapdeck token that has been set

Usage

```
mapdeck_tokens()
```

mapdeck_update	<i>Mapdeck update</i>
----------------	-----------------------

Description

Update a Mapdeck map in a shiny app. Use this function whenever the map needs to respond to reactive content.

Usage

```
mapdeck_update(
  data = NULL,
  map_id,
  session = shiny::getDefaultReactiveDomain(),
  deferUntilFlush = TRUE,
  map_type = c("mapdeck_update", "google_map_update")
)
```

Arguments

data	data to be used in the layer. All coordinates are expected to be EPSG:4326 (WGS 84) coordinate system
map_id	string containing the output ID of the map in a shiny application.
session	the Shiny session object to which the map belongs; usually the default value will suffice.
deferUntilFlush	indicates whether actions performed against this instance should be carried out right away, or whether they should be held until after the next time all of the outputs are updated; defaults to TRUE.
map_type	either mapdeck_update or google_map_update

mapdeck_view	<i>Mapdeck view</i>
--------------	---------------------

Description

Changes the view of the of the map

Usage

```
mapdeck_view(
  map,
  location = NULL,
  zoom = NULL,
  pitch = NULL,
  bearing = NULL,
  duration = NULL,
  transition = c("linear", "fly")
)
```

Arguments

map	a mapdeck map object
location	unnamed vector of lon and lat coordinates (in that order)
zoom	zoom level of the map
pitch	the pitch angle of the map
bearing	bearing of the map between 0 and 360
duration	time in milliseconds of the transition
transition	type of transition

melbourne	<i>Polygons in and around Melbourne</i>
-----------	---

Description

A data set containing statistical area 2 regions of central (and surrounds) Melbourne.

Usage

```
melbourne
```

Format

An sfencoded and data frame object with 41 observations and 8 variables. See library googlePoly-lines for information on sfencoded objects

melbourne_mesh	<i>Melbourne Mesh</i>
----------------	-----------------------

Description

A mesh3d object of Melbourne

Usage

melbourne_mesh

Format

An object of class mesh3d (inherits from shape3d) of length 6.

roads	<i>Roads in central Melbourne</i>
-------	-----------------------------------

Description

A simple feature sf object of roads in central Melbourne

Usage

roads

Format

An sf and data frame object with 18286 observations and 16 variables

Details

Obtained from <https://www.data.gov.au> and distributed under the Creative Commons 4 License <https://creativecommons.org/licenses/by/4.0/>

road_safety	<i>road_safety</i>
-------------	--------------------

Description

A data.frame of counts of traffic accidents in the UK

Usage

```
road_safety
```

Format

An object of class `data.frame` with 19139 rows and 2 columns.

set_token	<i>Set Token</i>
-----------	------------------

Description

Sets an access token so it's available for all mapdeck calls. See details

Usage

```
set_token(token)
```

Arguments

token	Mapbox access token
-------	---------------------

Details

Use `set_token` to make access tokens available for all the `mapdeck()` calls in a session so you don't have to keep specifying the token argument each time

update_style	<i>update style</i>
--------------	---------------------

Description

update style

Usage

```
update_style(map, style)
```

Arguments

map	a mapdeck map object
style	the style of the map (see mapdeck_style)

%>%	<i>Pipe</i>
-----	-------------

Description

Uses the pipe operator (%>%) to chain statements. Useful for adding layers to a mapdeck map

Arguments

lhs, rhs	A mapdeck map and a layer to add to it
----------	--

Examples

```
token <- "your_api_token"
mapdeck(token = token) %>%
  add_scatterplot(
    data = capitals
    , lat = "lat"
    , lon = "lon"
    , radius = 100000
    , fill_colour = "country"
    , layer_id = "scatter_layer"
  )
```

Index

* datasets

- capitals, [80](#)
- city_trail, [81](#)
- geojson, [83](#)
- melbourne, [91](#)
- melbourne_mesh, [92](#)
- road_safety, [93](#)
- roads, [92](#)
- %>%, [94](#)

- add_animated_arc, [3](#)
- add_animated_line, [7](#)
- add_arc, [5](#), [10](#), [12](#), [20](#), [26](#), [30](#), [47](#), [50](#), [53](#), [58](#),
[62](#), [66](#), [74](#), [78](#)
- add_bitmap, [15](#)
- add_cesium, [16](#)
- add_column, [17](#)
- add_dependencies, [21](#)
- add_geojson, [22](#), [70](#), [85](#)
- add_greatcircle, [27](#)
- add_grid, [31](#)
- add_h3, [35](#), [86](#)
- add_heatmap, [38](#)
- add_hexagon, [40](#)
- add_i3s, [44](#)
- add_line, [45](#)
- add_mesh, [48](#)
- add_path, [51](#), [70](#)
- add_pointcloud, [56](#), [85](#)
- add_polygon, [59](#), [70](#), [85](#)
- add_scatterplot, [63](#), [70](#)
- add_screengrid, [67](#)
- add_sf, [70](#)
- add_terrain, [70](#)
- add_text, [72](#)
- add_title, [75](#)
- add_trips, [76](#)

- capitals, [80](#)
- city_trail, [81](#)

- clear_animated_arc, [81](#)
- clear_arc (clear_animated_arc), [81](#)
- clear_bitmap (clear_animated_arc), [81](#)
- clear_column (clear_animated_arc), [81](#)
- clear_geojson (clear_animated_arc), [81](#)
- clear_greatcircle (clear_animated_arc),
[81](#)
- clear_grid (clear_animated_arc), [81](#)
- clear_h3 (clear_animated_arc), [81](#)
- clear_h3_hexagon (clear_animated_arc),
[81](#)
- clear_heatmap (clear_animated_arc), [81](#)
- clear_hexagon (clear_animated_arc), [81](#)
- clear_legend, [82](#)
- clear_line (clear_animated_arc), [81](#)
- clear_mesh (clear_animated_arc), [81](#)
- clear_path (clear_animated_arc), [81](#)
- clear_pointcloud (clear_animated_arc),
[81](#)
- clear_polygon (clear_animated_arc), [81](#)
- clear_scatterplot (clear_animated_arc),
[81](#)
- clear_screengrid (clear_animated_arc),
[81](#)
- clear_terrain (clear_animated_arc), [81](#)
- clear_text (clear_animated_arc), [81](#)
- clear_title (clear_animated_arc), [81](#)
- clear_tokens, [83](#)
- clear_trips (clear_animated_arc), [81](#)

- geojson, [83](#)

- invoke_method (mapdeck_dispatch), [88](#)

- legend_element, [84](#), [89](#)
- light_settings, [23](#), [36](#), [49](#), [57](#), [61](#), [85](#)

- mapdeck, [85](#), [88](#)
- mapdeck-shiny, [87](#)
- mapdeck_dependencies, [87](#)

mapdeck_dispatch, 88
mapdeck_legend, 84, 88
mapdeck_style, 86, 89, 94
mapdeck_tokens, 90
mapdeck_update, 88, 90
mapdeck_view, 91
mapdeckOutput (mapdeck-shiny), 87
melbourne, 91
melbourne_mesh, 92

renderMapdeck (mapdeck-shiny), 87
road_safety, 93
roads, 92

set_token, 93

update_style, 94